

MATERIAL SAFETY 3M  
 DATA SHEET 3M Center  
 St. Paul, Minnesota  
 55144-1000  
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.  
 All rights reserved. Copying and/or downloading of this  
 information for the purpose of properly utilizing 3M products  
 is allowed provided that:  
 1) the information is copied in full with no changes unless  
 prior agreement is obtained from 3M, and  
 2) neither the copy nor the original is resold or otherwise  
 distributed with the intention of earning a profit thereon.

DIVISION: COMMERCIAL CARE DIVISION  
 TRADE NAME:

3M Brand CARPET EXTRACTION CLEANER  
 ID NUMBER/U.P.C.:  
 41-1500-1322-9 - - - 61-5000-9485-1 00-48011-05719-9  
 61-5001-1266-1 00-48011-18091-5  
 ISSUED: August 13, 2001  
 SUPERSEDES: May 25, 1999  
 DOCUMENT: 05-3149-1

1. INGREDIENT	C.A.S. NO.	PERCENT
WATER.....	7732-18-5	60 - 90
SODIUM TRIPOLYPHOSPHATE.....	7758-29-4	3 - 7
POLYOXYETHYLENE MONOOCTYLPHENYL ETHER...	9036-19-5	3 - 7
2-BUTOXYETHANOL.....	111-76-2	1 - 5
SODIUM XYLENE SULFONATE.....	1300-72-7	1 - 5

IN CASE OF EMERGENCY: THE NUMBERS AT THE TOP OF THIS PAGE PROVIDE 24  
 HOUR RESPONSE FROM ANY PHONE FOR ALL EMERGENCIES WITH THIS PRODUCT.

This product contains the following toxic chemical or chemicals subject to  
 the reporting requirements of Section 313 of Title III of the Emergency  
 Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:  
 2-BUTOXYETHANOL

2. PHYSICAL DATA
BOILING POINT:..... 212 F
VAPOR PRESSURE:..... N/D
VAPOR DENSITY:..... 4.0 Air=1
EVAPORATION RATE:..... N/D
SOLUBILITY IN WATER:..... complete
SPECIFIC GRAVITY:..... ca. 1.04 Water=1
PERCENT VOLATILE:..... 80 - 90 %
pH:..... 8.5
VISCOSITY:..... < 100 centipoise
MELTING POINT:..... N/A

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
2. PHYSICAL DATA (continued)  
-----

APPEARANCE AND ODOR:

Liquid, colorless to light amber color; pleasant fragrance

-----  
3. FIRE AND EXPLOSION HAZARD DATA  
-----

FLASH POINT:..... > 200 F  
FLAMMABLE LIMITS - LEL:..... N/D  
FLAMMABLE LIMITS - UEL:..... N/D  
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:

Water spray, Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None known.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 0 REACTIVITY: 0  
UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Not applicable

-----  
4. REACTIVITY DATA  
-----

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

None known.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Oxides of Sulfur, Oxides of Phosphorus, Irritant Vapors or Gases.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
5. ENVIRONMENTAL INFORMATION  
-----

SPILL RESPONSE:

Observe precautions from other sections. Ventilate area. Contain spill. Cover with inorganic absorbent material. Collect spilled material. Clean up residue with water. Place in a closed container.

RECOMMENDED DISPOSAL:

Incinerate in an industrial or commercial facility in the presence of a combustible material.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: ca. 27 gms/liter.  
VOC Less H2O & Exempt Solvents: N/D.

Since regulations vary, consult applicable regulations or authorities before disposal. In the event of an uncontrolled release of this material, the user should determine if the release qualifies as a reportable quantity. U.S. EPA Hazardous Waste Number = None (Not U.S. EPA Hazardous).

TSCA: All components used in the manufacture of this material are in compliance with the US TSCA inventory.

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

-----  
6. SUGGESTED FIRST AID  
-----

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
7. PRECAUTIONARY INFORMATION  
-----

EYE PROTECTION:  
Avoid eye contact.

SKIN PROTECTION:  
Avoid prolonged or repeated skin contact.

RECOMMENDED VENTILATION:  
Use with adequate dilution ventilation.

RESPIRATORY PROTECTION:  
Avoid prolonged breathing of vapors.

PREVENTION OF ACCIDENTAL INGESTION:  
Wash hands after handling and before eating.

RECOMMENDED STORAGE:  
Store in a cool place. Store away from heat. Keep container in well-ventilated area. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:  
Keep container tightly closed.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
WATER.....	NONE	NONE	NONE	NONE	
SODIUM TRIPOLYPHOSPHATE.....	NONE	NONE	NONE	NONE	
POLYOXYETHYLENE MONOOCTYLPHENYL ETHER.....	NONE	NONE	NONE	NONE	
2-BUTOXYETHANOL.....	25	PPM	TWA	ACGIH	Y
2-BUTOXYETHANOL.....	25	PPM	TWA	OSHAV	Y
		OSHA VACATED	PEL		
2-BUTOXYETHANOL.....	50	PPM	TWA	OSHA	Y
SODIUM XYLENE SULFONATE.....	NONE	NONE	NONE	NONE	

\* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL.  
Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
-----					
- NONE:	None	Established			

-----  
8. HEALTH HAZARD DATA  
-----

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

SKIN CONTACT:

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

May be absorbed through the skin and produce effects similiar to those caused by inhalation and/or ingestion.

INHALATION:

Single overexposure, above recommended guidelines, may cause:

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Single overexposure, above recommended guidelines, may cause:

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

Ingestion may cause:

Gastrointestinal Effects: signs/symptoms generally will include abdominal pain.

-----  
SECTION CHANGE DATES  
-----

HEADING	SECTION CHANGED SINCE	ISSUE
	May 25, 1999	

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.