

ITEM: 3KB83 - Remover Adhesive 24 Oz 18.4 oz Net

PICK REQ: 1215608769

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: B0893

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - B0893

Associated Grainger Item: 3KB83 - Remover Adhesive 24 Oz 18.4 oz Net

3M

MATERIAL SAFETY DATA SHEET

3M(TM) ADHESIVE REMOVER 6040 / 6041 (AEROSOL)

09/13/2005

3M

MATERIAL SAFETY DATA SHEET

COPYRIGHT, 2005, 3M COMPANY. ALL RIGHTS RESERVED. COPYING AND/OR DOWNLOADING OF THIS INFORMATION FOR THE PURPOSE OF PROPERLY UTILIZING 3M PRODUCTS IS ALLOWED PROVIDED THAT:

- (1) THE INFORMATION IS COPIED IN FULL WITH NO CHANGES UNLESS PRIOR WRITTEN AGREEMENT IS OBTAINED FROM 3M, AND
- (2) NEITHER THE COPY NOR THE ORIGINAL IS RESOLD OR OTHERWISE DISTRIBUTED WITH THE INTENTION OF EARNING A PROFIT THEREON.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) ADHESIVE REMOVER 6040 / 6041 (AEROSOL)

MANUFACTURER: 3M

DIVISION: INDUSTRIAL ADHESIVES AND TAPES

ADDRESS:
3M CENTER
ST. PAUL, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 OR (651) 737-6501 (24 HOURS)

ISSUE DATE: 09/13/2005

SUPERCEDES DATE: 12/14/2004

DOCUMENT GROUP: 08-6485-0

PRODUCT USE:
SPECIFIC USE: ADHESIVE REMOVER

SECTION 2: INGREDIENTS

INGREDIENT	C.A.S. NO.	% BY WT
CITRUS EXTRACT	8028-48-6	80 - 90
PROPANE	74-98-6	10 - 20

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW:

ODOR, COLOR, GRADE: CLEAR, PALE YELLOW, SWEET ODOR

GENERAL PHYSICAL FORM: GAS

IMMEDIATE HEALTH, PHYSICAL, AND ENVIRONMENTAL HAZARDS:
CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE AND EXPLODE.
EXTREMELY FLAMMABLE LIQUID AND VAPOR. AEROSOL CONTAINER CONTAINS FLAMMABLE MATERIAL UNDER PRESSURE. MAY CAUSE ALLERGIC SKIN REACTION.

3.2 POTENTIAL HEALTH EFFECTS:

EYE CONTACT:
MODERATE EYE IRRITATION:
SIGNS/SYMPTOMS MAY INCLUDE REDNESS, SWELLING, PAIN, TEARING, AND BLURRED OR HAZY VISION.

SKIN CONTACT:
MODERATE SKIN IRRITATION:
SIGNS/SYMPTOMS MAY INCLUDE LOCALIZED REDNESS, SWELLING, ITCHING, AND DRYNESS.

PROLONGED OR REPEATED EXPOSURE MAY CAUSE:
ALLERGIC SKIN REACTION (NON-PHOTO INDUCED):
SIGNS/SYMPTOMS MAY INCLUDE REDNESS, SWELLING, BLISTERING, AND ITCHING.

INHALATION:
RESPIRATORY TRACT IRRITATION:
SIGNS/SYMPTOMS MAY INCLUDE COUGH, SNEEZING, NASAL DISCHARGE, HEADACHE, HOARSENESS, AND NOSE AND THROAT PAIN.

INTENTIONAL CONCENTRATION AND INHALATION MAY BE HARMFUL OR FATAL.

INGESTION:
GASTROINTESTINAL IRRITATION:
SIGNS/SYMPTOMS MAY INCLUDE ABDOMINAL PAIN, STOMACH UPSET, NAUSEA, VOMITING AND DIARRHEA.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS:

CHEMICAL ANALYSIS OF 3M CITRUS BASE ADHESIVE REMOVER YIELDED THE FOLLOWING DATA:
CHLORIDE: <10 PPM
FLUORIDE: <1 PPM
SULFUR: <4 PPM
TOTAL HALOGEN: <10 PPM.

SECTION 4: FIRST AID MEASURES

1.1 FIRST AID PROCEDURES:
THE FOLLOWING FIRST AID RECOMMENDATIONS ARE BASED ON AN ASSUMPTION THAT APPROPRIATE PERSONAL AND INDUSTRIAL HYGIENE PRACTICES ARE FOLLOWED.

EYE CONTACT:
FLUSH EYES WITH LARGE AMOUNTS OF WATER. IF SIGNS/SYMPTOMS PERSIST, GET MEDICAL ATTENTION.

SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING AND SHOES. IMMEDIATELY FLUSH SKIN WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING AND CLEAN SHOES BEFORE REUSE.

INHALATION:
REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS DEVELOP, GET MEDICAL ATTENTION.

IF SWALLOWED:
DO NOT INDUCE VOMITING UNLESS INSTRUCTED TO DO SO BY MEDICAL PERSONNEL. GIVE VICTIM TWO GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENTION.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES:

AUTOIGNITION TEMPERATURE: NO DATA AVAILABLE

FLASH POINT: -50.00 DEG. F

FLAMMABLE LIMITS - LEL: 2.1 % VOLUME (DETAILS: CONDITIONS: PROPANE)
FLAMMABLE LIMITS - UEL: 9.5 % VOLUME (DETAILS: CONDITIONS: PROPANE)

5.2 EXTINGUISHING MEDIA:
USE FIRE EXTINGUISHERS WITH CLASS B EXTINGUISHING AGENTS (E.G., DRY CHEMICAL, CARBON DIOXIDE).

5.3 PROTECTION OF FIRE FIGHTERS:

SPECIAL FIRE FIGHTING PROCEDURES:
WEAR FULL PROTECTIVE EQUIPMENT (BUNKER GEAR) AND A SELF-CONTAINED BREATHING APPARATUS (SCBA).

UNUSUAL FIRE AND EXPLOSION HAZARDS:
CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE AND EXPLODE. EXTREMELY FLAMMABLE LIQUID AND VAPOR. AEROSOL CONTAINER CONTAINS FLAMMABLE MATERIAL UNDER PRESSURE.

NOTE:
SEE STABILITY AND REACTIVITY (SECTION 10) FOR HAZARDOUS COMBUSTION AND THERMAL DECOMPOSITION INFORMATION.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:
REFER TO OTHER SECTIONS OF THIS MSDS FOR INFORMATION REGARDING PHYSICAL AND HEALTH HAZARD, RESPIRATORY PROTECTION, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT. CALL 3M-HELPS LINE (1-800-364-3577) FOR MORE INFORMATION ON HANDLING AND MANAGING THE SPILL. EVACUATE UNPROTECTED AND UNTRAINED PERSONNEL FROM HAZARD AREA. THE SPILL SHOULD BE CLEANED UP BY QUALIFIED PERSONNEL. REMOVE ALL IGNITION SOURCES SUCH AS FLAMES, SMOKING MATERIALS, AND ELECTRICAL SPARK SOURCES. USE ONLY NON-SPARKING TOOLS. VENTILATE THE AREA WITH FRESH AIR. IF POSSIBLE, SEAL LEAKING CONTAINER. PLACE LEAKING CONTAINERS IN A WELL-VENTILATED AREA, PREFERABLY AN OPERATING EXHAUST HOOD, OR IF NECESSARY OUTDOORS ON AN IMPERMEABLE SURFACE UNTIL APPROPRIATE PACKAGING FOR THE LEAKING CONTAINER OR ITS CONTENTS IS AVAILABLE. CLOSE CYLINDER. IF THE CYLINDER CAN'T BE CLOSED, PLACE IN A WELL-VENTILATED AREA, PREFERABLY AN OPERATING EXHAUST HOOD, OR IF NECESSARY OUTDOORS. DISPOSE OF COLLECTED MATERIAL AS SOON AS POSSIBLE.

IN THE EVENT OF A RELEASE OF THIS MATERIAL, THE USER SHOULD DETERMINE IF THE RELEASE QUALIFIES AS REPORTABLE ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING:
DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. WASH EXPOSED AREAS THOROUGHLY WITH SOAP AND WATER. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME, PILOT LIGHTS AND OTHER SOURCES OF IGNITION. AVOID EYE CONTACT WITH VAPORS, MISTS, OR SPRAY. KEEP OUT OF THE REACH OF CHILDREN. VAPORS MAY IGNITE EXPLOSIVELY. MAY CAUSE FLASH FIRE. PREVENT BUILD-UP OF VAPORS - OPEN ALL WINDOWS AND DOORS. MAINTAIN VAPOR CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS. USE ONLY WITH CROSS-VENTILATION. WITHOUT ADEQUATE VENTILATION, VAPORS MAY SETTLE IN LOW-LYING AREAS. KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. DO NOT SMOKE OR IGNITE MATCHES, LIGHTERS, ETC.

7.2 STORAGE:
STORE AWAY FROM ACIDS. STORE AWAY FROM HEAT. STORE OUT OF DIRECT SUNLIGHT. KEEP CONTAINER IN WELL-VENTILATED AREA.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS:
USE WITH APPROPRIATE LOCAL EXHAUST VENTILATION. PROVIDE APPROPRIATE LOCAL EXHAUST VENTILATION ON OPEN CONTAINERS. USE WITH FUNCTIONING SPRAY BOOTH OR LOCAL EXHAUST. DO NOT USE IN A CONFINED AREA OR AREAS WITH LITTLE OR NO AIR MOVEMENT. USE GENERAL DILUTION VENTILATION AND/OR LOCAL EXHAUST VENTILATION TO CONTROL AIRBORNE EXPOSURES TO BELOW OCCUPATIONAL EXPOSURE LIMITS AND/OR CONTROL MIST, VAPOR, OR SPRAY. IF VENTILATION IS NOT ADEQUATE, USE RESPIRATORY PROTECTION EQUIPMENT. DO NOT USE IN A CONFINED AREA OR AREAS WITH LITTLE OR NO AIR MOVEMENT. IF EXHAUST VENTILATION IS NOT ADEQUATE, USE APPROPRIATE RESPIRATORY PROTECTION. PROVIDE VENTILATION ADEQUATE TO CONTROL VAPOR CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS AND/OR CONTROL SPRAY OR MIST.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE):

8.2.1 EYE/FACE PROTECTION: AVOID EYE CONTACT WITH VAPORS, MISTS, OR SPRAY.

THE FOLLOWING EYE PROTECTION(S) ARE RECOMMENDED:
SAFETY GLASSES WITH SIDE SHIELDS.

8.2.2 SKIN PROTECTION:

AVOID SKIN CONTACT. SELECT AND USE GLOVES AND/OR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT BASED ON THE RESULTS OF AN EXPOSURE ASSESSMENT. CONSULT WITH YOUR GLOVE AND/OR PROTECTIVE CLOTHING MANUFACTURER FOR SELECTION OF APPROPRIATE COMPATIBLE MATERIALS.

8.2.3 RESPIRATORY PROTECTION:

AVOID BREATHING OF VAPORS, MISTS OR SPRAY.
SELECT ONE OF THE FOLLOWING NIOSH APPROVED RESPIRATORS BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS AND IN ACCORDANCE WITH OSHA REGULATIONS:
HALF FACEPIECE AIR-PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES.
CONSULT THE CURRENT 3M RESPIRATORY SELECTION GUIDE FOR ADDITIONAL INFORMATION OR CALL 1-800-243-4630 FOR 3M TECHNICAL ASSISTANCE.

8.2.4 PREVENTION OF SWALLOWING:

DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. WASH EXPOSED AREAS THOROUGHLY WITH SOAP AND WATER.

8.3 EXPOSURE GUIDELINES:

INGREDIENT	AUTHORITY	TYPE	LIMIT	ADDITIONAL INFORMATION
PROPANE	ACGIH	TWA	1000 PPM	
PROPANE	OSHA	TWA	1000 PPM	TABLE Z-1

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

CMRG: CHEMICAL MANUFACTURER RECOMMENDED GUIDELINE

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

AIHA:

AMERICAN INDUSTRIAL HYGIENE ASSOCIATION WORKPLACE ENVIRONMENTAL EXPOSURE LEVEL (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

ODOR, COLOR, GRADE: CLEAR, PALE YELLOW, SWEET ODOR

GENERAL PHYSICAL FORM: GAS

AUTOIGNITION TEMPERATURE: NO DATA AVAILABLE

FLASH POINT: -50.00 DEG. F

FLAMMABLE LIMITS - LEL: 2.1 % VOLUME (DETAILS: CONDITIONS: PROPANE)

FLAMMABLE LIMITS - UEL: 9.5 % VOLUME (DETAILS: CONDITIONS: PROPANE)

VAPOR DENSITY: NOT APPLICABLE

VAPOR PRESSURE: 28 MMHg (@ 20 DEG. C)
(DETAILS: COMPOSITE VAPOR PRESSURE (CALCULATED))

SPECIFIC GRAVITY: 0.793 (REF STD: WATER=1)

pH: NOT APPLICABLE

MELTING POINT: NO DATA AVAILABLE

SOLUBILITY IN WATER: NIL

EVAPORATION RATE: NO DATA AVAILABLE

VOLATILE ORGANIC COMPOUNDS: APPROXIMATELY 100 %
(TEST METHOD: CALCULATED SCAQMD RULE 443.1)

PERCENT VOLATILE: APPROXIMATELY 100 % WEIGHT

VOC LESS H2O & EXEMPT SOLVENTS: APPROXIMATELY 100 %
(TEST METHOD: CALCULATED SCAQMD RULE 443.1)

VISCOSITY: NOT APPLICABLE

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE.

MATERIALS AND CONDITIONS TO AVOID: HEAT

HAZARDOUS POLYMERIZATION: HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

SUBSTANCE	CONDITION
ALDEHYDES	DURING COMBUSTION
HYDROCARBONS	DURING COMBUSTION
CARBON MONOXIDE	DURING COMBUSTION
CARBON DIOXIDE	DURING COMBUSTION
KETONES	NOT SPECIFIED

SECTION 11: TOXICOLOGICAL INFORMATION

PLEASE CONTACT THE ADDRESS LISTED IN SECTION 1 OF THIS MSDS FOR TOXICOLOGICAL INFORMATION ON THIS MATERIAL AND/OR ITS COMPONENTS.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: NOT DETERMINED.

CHEMICAL FATE INFORMATION: NOT DETERMINED.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

INCINERATE IN A PERMITTED HAZARDOUS WASTE INCINERATOR. AS A DISPOSAL ALTERNATIVE, DISPOSE OF WASTE PRODUCT IN A PERMITTED HAZARDOUS WASTE FACILITY.

THE FACILITY SHOULD BE EQUIPPED TO HANDLE GASEOUS WASTE.
RECYCLE EMPTY AEROSOL CONTAINERS WHERE AVAILABLE.

EPA HAZARDOUS WASTE NUMBER (RCRA): D001 (IGNITABLE)

SINCE REGULATIONS VARY, CONSULT APPLICABLE REGULATIONS OR AUTHORITIES BEFORE DISPOSAL.

SECTION 14: TRANSPORT INFORMATION

ID NUMBER(S):

62-4667-2925-8, 62-4667-2928-2, 62-4667-2930-8, 62-4667-2935-7,
62-4667-4930-6, 62-4667-4932-2, 62-4667-4935-5

PLEASE CONTACT THE EMERGENCY NUMBERS LISTED IN SECTION 1 OF THIS MSDS FOR TRANSPORTATION INFORMATION FOR THIS MATERIAL.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

311/312 HAZARD CATEGORIES:

FIRE HAZARD: YES

PRESSURE HAZARD: YES

REACTIVITY HAZARD: NO

IMMEDIATE HAZARD: YES

DELAYED HAZARD: NO

STATE REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

CHEMICAL INVENTORIES:

THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE CHEMICAL NOTIFICATION REQUIREMENTS OF TSCA.

ALL APPLICABLE CHEMICAL INGREDIENTS IN THIS MATERIAL ARE LISTED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICAL SUBSTANCES (EINECS), OR ARE EXEMPT POLYMERS WHOSE MONOMERS ARE LISTED ON EINECS.

CONTACT 3M FOR MORE INFORMATION.

INTERNATIONAL REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

THIS MSDS HAS BEEN PREPARED TO MEET THE U.S. OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NEPA HAZARD CLASSIFICATION:

HEALTH 2

FLAMMABILITY 4

REACTIVITY 1

SPECIAL HAZARDS NONE

AEROSOL STORAGE CODE: 2

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD RATINGS ARE DESIGNED FOR USE BY EMERGENCY RESPONSE PERSONNEL TO ADDRESS THE HAZARDS THAT ARE PRESENTED BY SHORT-TERM, ACUTE EXPOSURE TO A MATERIAL UNDER CONDITIONS OF FIRE, SPILL, OR SIMILAR EMERGENCIES. HAZARD RATINGS ARE PRIMARILY BASED ON THE INHERENT PHYSICAL AND TOXIC PROPERTIES OF THE MATERIAL BUT ALSO INCLUDE THE TOXIC PROPERTIES OF COMBUSTION OR DECOMPOSITION PRODUCTS THAT ARE KNOWN TO BE GENERATED IN SIGNIFICANT QUANTITIES.

REVISION CHANGES: COPYRIGHT WAS MODIFIED.

SECTION 3: IMMEDIATE PHYSICAL HAZARD(S) WAS MODIFIED.

SECTION 3: POTENTIAL EFFECTS FROM SKIN CONTACT INFORMATION WAS MODIFIED.

SECTION 3: POTENTIAL EFFECTS FROM INHALATION INFORMATION WAS MODIFIED.

SECTION 3: POTENTIAL EFFECTS FROM INGESTION INFORMATION WAS MODIFIED.

SECTION 5: UNUSUAL FIRE AND EXPLOSION HAZARD INFORMATION WAS MODIFIED.

SECTION 6: RELEASE MEASURES INFORMATION WAS MODIFIED.

SECTION 7: HANDLING INFORMATION WAS MODIFIED.

SECTION 7: STORAGE INFORMATION WAS MODIFIED.

SECTION 8: ENGINEERING CONTROLS INFORMATION WAS MODIFIED.

SECTION 8: EYE/FACE PROTECTION PHRASE WAS MODIFIED.

SECTION 13: WASTE DISPOSAL METHOD INFORMATION WAS MODIFIED.

SECTION 4:
FIRST AID FOR INGESTION (SWALLOWING) - DECONTAMINATION - WAS MODIFIED.

SECTION 4:
FIRST AID FOR INGESTION (SWALLOWING) - MEDICAL ASSISTANCE - WAS MODIFIED.

SECTION 15: 311/312 DELAYED HAZARD SCORE WAS MODIFIED.

SECTION 3: IMMEDIATE SKIN HAZARD(S) WAS ADDED.

SECTION 9: VAPOR PRESSURE VALUE WAS ADDED.

SECTION 3: OTHER POTENTIAL HEALTH EFFECTS HEADING WAS DELETED.

SECTION 3: IMMEDIATE OTHER HAZARD(S) WAS DELETED.

SECTION 3: OTHER HEALTH EFFECTS INFORMATION WAS DELETED.

DISCLAIMER:

THE INFORMATION IN THIS MATERIAL SAFETY DATA SHEET (MSDS) IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.

USER IS RESPONSIBLE FOR DETERMINING WHETHER THE 3M PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION. GIVEN THE VARIETY OF FACTORS THAT CAN AFFECT THE USE AND APPLICATION OF A 3M PRODUCT, SOME OF WHICH ARE UNIQUELY WITHIN THE USER'S KNOWLEDGE AND CONTROL, IT IS ESSENTIAL THAT THE USER EVALUATE THE 3M PRODUCT TO DETERMINE WHETHER IT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION.

3M PROVIDES INFORMATION IN ELECTRONIC FORM AS A SERVICE TO ITS CUSTOMERS. DUE TO THE REMOTE POSSIBILITY THAT ELECTRONIC TRANSFER MAY HAVE RESULTED IN ERRORS, OMISSIONS OR ALTERATIONS IN THIS INFORMATION, 3M MAKES NO REPRESENTATIONS AS TO ITS COMPLETENESS OR ACCURACY. IN ADDITION, INFORMATION OBTAINED FROM A DATABASE MAY NOT BE AS CURRENT AS THE INFORMATION IN THE MSDS AVAILABLE DIRECTLY FROM 3M.

3M MSDSS ARE AVAILABLE AT WWW.3M.COM