

440

STA-LUBE INC -- SOLUBLE OIL, AB7A081

MSDS Safety Information

FSC: 9150
MSDS Date: 05/01/1991
MSDS Num: BLSMY
LIIN: 00N022680
Product ID: SOLUBLE OIL, AB7A081
MFN: 01
Responsible Party
Cage: 33876
Name: STA-LUBE INC
Address: 3039 ANA STREET
City: RANCHO DOMINGUEZ CA 90221
Info Phone Number: 213-537-5650
Emergency Phone Number: 213-664-2121 800-424-9300 (CHEMTREC)
Published: Y

Contractor Summary

Cage: 33876
Name: STA-LUBE INC
Address: 3039 ANA ST
City: RANCHO DOMINGUEZ (PART OF COMPTON) CA 90221
Phone: 310-664-2121/800-424-9300 (CHEMTREC)

Ingredients

Name: FIRST AID PROC:THIS MATERIAL IS A COMPLEX LIQUID PETROLEUM HYDROCARBON
BASED MIXTURE WITH A LOW ORDER OF TOXICITY.

Name: ING 4:DO NOT CUT, WELD, DRILL, OR EXPOSE TO HEAT OR FLAME. VAPORS MAY BE
HAZARDOUS.

Cas: 64741-97-5
RTECS #: PY8041000
Name: MINERAL OIL, PETRO DISTILLATES, SOLVENT-REFINED (MILD) LIGHT NAPHTHENIC;
(SOLVENT REFINED NAPHTHENIC DISTILLATES)
OSHA PEL: 5 MG/M3,MIN OIL MIST
ACGIH TLV: 5 MG/M3,MIN OIL MIST

Cas: 141-43-5
RTECS #: KJ5775000
Name: ETHANOLAMINE
OSHA PEL: 3 PPM/6 STEL
ACGIH TLV: 3 PPM/6 STEL; 9192

Cas: 26952-21-6
RTECS #: NS7700000
Name: ISOCTYL ALCOHOL
OSHA PEL: S, 50 PM
ACGIH TLV: S, 50 PPM; 9192

Name: SUPP DATA:BEFORE REUSE.KEEP CLSD & DO NOT USE TO STORE OR MIX OTHER
MATLS BEFORE HAVING COMMERCIALY CLEANED.(SEE ING 5)

Health Hazards Data

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO

OSHA: NO

Effects of Exposure: CONTACT WILL IRRITATE EYES. PROLONGED CONTACT MAY IRRITATE SKIN. MIST, FUMES, OR VAPOR, IF GENERATED, MAY IRRITATE EYES AND UPPER RESPIRATORY TRACT. EYE: CAN CAUSE IRRITATION. DIRECT CONTACT OR EXPOSURE TO MIST/FUMES/VAPOR WHICH MAY BE GENERATED IF HEATED MAY CAUSE BURNING, TEARING & REDNESS. SKIN: MAY CAUSE IRRITATION. (EFFECTS OF OVEREXPOSURE)

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptoms Of Overexposure: HEALTH HAZARD: PROLONGED OR REPEATED CONTACT MAY CAUSE BURNING, REDNESS, AND DERMATITIS. INHALATION: EXPOSURE TO MIST OR FUMES OR VAPOR WHICH MAY BE GENERATED IF HEATED MAY IRRITATE NOSE, THROAT, AND UPPER RESPIRATORY TRACT. INGESTION: CAN CAUSE IRRITATION OF STOMACH & INTESTINAL TRACT. CHRONIC: NONE KNOWN.

Medical Condition Aggravated By Exposure: PRE-EXISTING SKIN CONDITIONS. PRE-EXISTING RESPIRATORY CONDITIONS IF MIST, FUMES, OR VAPOR ARE GENERATED.

First Aid: EYE: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION DEVELOPS, GET MEDICAL. SKIN: REMOVE CONTAMINATED CLOTHING & WIPE FROM SKIN. THOROUGHLY WASH WITH SOAP & WATER. USE WATERLESS SKIN CLEANSER, IF NECESSARY. IF IRRITATION DEVELOPS & PERSISTS, GET MEDICAL. INHALATION: IF NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE GIVEN. MOVE TO FRESH AIR. IF SYMPTOMS OF EXPOSURE DEVELOP, GET MEDICAL. INGESTION: IF CONSCIOUS, GIVE MILK/WATER TO DRINK. NOTE TO MEDICAL: (SEE SECTION 6)

=====
Handling and Disposal
=====

Spill Release Procedures: WEAR RECOMMENDED PROTECTIVE CLOTHING/EQUIP & PROVIDE ADEQUATE VENTILATION. DO NOT ALLOW SPILL TO ENTER SEWERS/STREAMS OR SURFACE WATERS. DIKE & CONTAIN SPILLS. PICK UP LARGE SPILLS FOR LATER RECLAMATION & DISPOSAL. USE AN INERT ADSORBENT TO PICK UP RESIDUE/SMALL SPILLS & COLLECT FOR LATER DISPOSAL.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. EMPTY TANKS AND CONTAINERS SHOULD BE COMMERCIALY CLEANED AND RECONDITIONED BEFORE REUSE.

Handling And Storage Precautions: STORE IN CLOSED CONTAINERS IN A COOL, DRY, WELL-VENTILATED AREA AWAY FROM HEAT AND STRONG OXIDIZING AGENTS. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions: ROUTINE OPERATIONS: USE IN WELL-VENTILATED AREA & WEAR RECOMMENDED PROTECTIVE CLOTHING & EQUIP. AVOID BREATHING MIST/FUMES/VAPOR GENERATED WHEN MATERIAL HEATED. AVOID Prolonged SKIN CONTACT. LABEL ALL UNATTENDED CONTAINERS. NON-ROUTINE OPERATIONS: OPERATIONS SUCH AS MAINTENANCE, REPAIR, (SUPPLEMENTAL DATA)

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: COC

Flash Point Text: >400F, >204C

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, & WATER SPRAY. WATER SPRAY OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FULL FACE). USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS, DILUTE/DISPERSE VAPORS, PROTECT PERSONNEL & FLUSH (SEE SUPPLEMENTAL DATA)

Unusual Fire/Explosion Hazard: MATERIAL CAN IGNITE & BURN WHEN HEATED ABOVE FLASH POINT. EMPTY TANKS OR CONTAINERS RETAIN MATERIAL RESIDUE & MAY, IF HEATED, GENERATE VAPORS WHICH CAN IGNITE/EXPLODE.

=====
Control Measures
=====

Respiratory Protection: ALL RESPIRATORS MUST BE NIOSH/MSHA APPROVED. MAY BE NECESSARY TO MINIMIZE EXPOSURE TO MIST/FUMES/VAPOR. WEAR AIR-PURIFYING RESPIRATOR WITH ORGANIC VAPOR/PARTICULATE FILTER CARTRIDGE IN SITUATIONS WHERE VAPOR, FUME/MIST CONCENTRATION MAY EXCEED RECOMMENDED EXPOSURE LIMITS. USE SCBA FOR EMERGENCY.

Ventilation: GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST IS RECOMMENDED TO MAINTAIN MIST, FUME, OR VAPOR CONCENTRATION BELOW RECOMMENDED EXPOSURE LIMIT.

Protective Gloves: IMPERMEABLE GLOVES (FULL FACE).

Eye Protection: CHEMICAL WORKERS GOGGLES (FULL FACE).

Other Protective Equipment: EYE WASH & SOURCE OF RUNNING WATER. BARRIER CREAMS SPECIFIC FOR PETROLEUM BASED MATERIALS WHEN GLOVES ARE IMPRACTICAL.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. CLEAN OR LAUNDRY

CONTAMINATED SHOES & CLOTHING BEFORE REUSE.
Supplemental Safety and Health: FIRE FIGHT PROC:UNIGNIT MATL SPILLS AWAY FROM
FIRE. OTHER PREC:CLEAN-UP, OR SAMPLING INCR POTNTL FOR EXPOS TO MATL. PERS
INVOLVED IN THESE TYPES OF OPERS SHOULD WEAR PROT EQUIP & CLTHG &
EXERCISE SPE CIAL PRECS TO AVOID EXPOS OF MATL. MISUSE OF EMPTY CNTNRS CAN
BE HAZ. COMPLETELY DRAIN & COMMERCIALY CLEAN (SEE ING 4)

=====
Physical/Chemical Properties
=====

HCC: V6
B.P. Text: >600F,>316C
Vapor Pres: NEGLIGIBLE
Vapor Density: HVR/AIR
Spec Gravity: 0.85-0.95
Evaporation Rate & Reference: NEGLIGIBLE
Solubility in Water: EMULSIFIES
Appearance and Odor: AMBER COLORED LIQ W/PETROLEUM ODOR.
Percent Volatiles by Volume: NEG

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.
Materials To Avoid: STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products: BURNING PRODUCES CO, CO*2 & POSSIBLE TRACE
AMOUNTS OF SO*X & NO*X.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT.

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: 33876
Trans ID NO: 27329
Product ID: SOLUBLE OIL, AB7A081
MSDS Prepared Date: 05/01/1991
Review Date: 01/30/1992
MFN: 1
Multiple KIT Number: 0
Review IND: Y
Additional Data: NOT REGULATED FOR TRANSPORTATION

=====
Detail DOT Information
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

Detail AFI Information
=====

AFI PSN Code: ZZZ
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

HAZCOM Label
=====

Product ID: SOLUBLE OIL, AB7A081
Cage: 33876
Company Name: STA-LUBE INC
Street: 3039 ANA ST
City: RANCHO DOMINGUEZ (PART OF COMPTON) CA
Zipcode: 90221
Health Emergency Phone: 213-664-2121 800-424-9300 (CHEMTREC)
Label Required IND: Y
Date Of Label Review: 12/09/1991
Status Code: C
Label Date: 12/09/1991
Origination Code: G
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: WARNING
Respiratory Protection IND: YES
Health Hazard: Slight
Contact Hazard: Moderate
Fire Hazard: None
Reactivity Hazard: Slight

Hazard And Precautions: ACUTE: THIS MATERIAL MAY CAUSE SKIN IRRITATION.
PROLONGED OR REPEATED CONTACT MAY CAUSE BURNING, REDNESS AND DERMATITIS. MAY
CAUSE EYE IRRITATION. DIRECT CONTACT OR EXPOSURE TO MIST/FUMES/VAPOR WHICH
MAY BE GENERATED IF HEATED MAY CAUSE BURNING, TEARING, AND REDNESS.
INHALATION OF MIST/FUMES/VAPOR GENERATED WHEN HEATED MAY IRRITATE NOSE,
THROAT, AND UPPER RESPIRATORY TRACT. INGESTION CAN CAUSE IRR ITATION OF
STOMACH AND INTESTINAL TRACT. CHRONIC: NONE KNOWN BY MANUFACTURER.
=====

Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.