

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57746
 PART NUMBER: C-13
 PRODUCT NAME: SUPER GLASS GLEAM (REVISED 07/08/98)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES ADDRESS: 1910 SO. YALE ST. SANTA ANA, CA 92704 EMERGENCY TELEPHONE NUMBER: (800)424-9300 INFORMATION TELEPHONE NUMBER: (714)540-3850 DATE PREPARED: 07/08/98	HMIS RATING: HEALTH: 1 FIRE: 1 REACTIVITY: 0 PERSONAL PROTECTION: B	NFPA RATING: <div style="text-align: center;"> </div> HEALTH: 1 FIRE: 1 NONE: 0 SPEC.HAZ. REACT.: 0
--	---	---

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
67-63-0	ISOPROPYL ALCOHOL					400ppm	400ppm		5-10
111-76-2	GLYCOL ETHER * *SEE SECTION IX				Y	25ppm	25ppm		1-5

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	212° F	SPECIFIC GRAVITY (H ₂ O=1)	0.99000
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AV
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	TOTAL		
APPEARANCE AND ODOR:	PINK LIQUID. ALCOHOL ODOR.		
OTHER INFORMATION:	N/AP		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/AV	FLAMMABLE LIMITS:	LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA: CO 2, DRY CHEMICAL OR FOAM.			
SPECIAL FIRE FIGHTING PROCEDURES: N/AP			
UNUSUAL FIRE FIGHTING PROCEDURES: N/AP			

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CO, CO 2.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION
HEALTH HAZARDS (ACUTE AND CHRONIC): EXCESSIVE INHALATION MAY CAUSE NAUSEA OR DIZZINESS.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57746
 PRODUCT NAME: C-13 SUPER GLASS GLEAM (REVISED 07/08/98)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP SPILLED LIQUID.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GENERAL

PERSONAL PROTECTIVE EQUIPMENT: SAFETY GLASSES AND CHEMICAL RESISTANT GLOVES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: * CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) AND 40 CFR PART 372.

GLYCOL ETHER CAS# 111-76-2 1-5%

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = CLEANING LIQUID

PACKING GROUP = NONE

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
 N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|-------------------|----------------|
| 1. | WATER | CAS# 7732-18-5 |
| 2. | ISOPROPYL ALCOHOL | CAS# 67-63-0 |
| 3. | GLYCOL ETHER | CAS# 111-76-2 |
| 4. | PERFUME | MIXTURE |

V. O. C. CONTENT: 144 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN CARCINOGEN AS SET FORTH BY I. A. R. C. OR OTHER REGULATORY AGENCY.
