



## Valspar® Premium Enamel Spray Paint



### Product Description

Premium spray that delivers a flawless, fast drying finish. Can be used on metal, wood, plastic and many more surfaces. Available in primary and designer colors. Three sheens – gloss, satin and matte. **Tip:** Add Valspar's® Premium Primer and Clear topcoat to provide a tough protective coating that withstands weather, corrosion and water.

### Features

- Interior/exterior uses
- Comfort touch pad spray button
- Fast drying
- Pinch and pull cap
- Higher gloss than previous formula
- Excellent adhesion to metals such as aluminum and steel

### Colors Information

Gloss White	65000	Satin Mint	65038
Satin White	65001	Gloss Pewter Gray	65039
Flat White	65002	Satin Window Gray	65040
Gloss Antique White	65003	Gloss Medium Gray	65041
Gloss Almond	65004	Satin Urban Beige	65042
Satin Porcelain	65005	Flat Butterscotch	65043
Flat Ice Cream	65006	Satin Java Brown	65044
Satin Lemon	65007	Gloss Buckeye Brown	65045
Satin Sunflower	65008	Flat Velvet Brown	65046
Satin Yellow Crème	65009	Satin Cappuccino	65047
Gloss Bumblebee	65010	Gloss Black	65048
Gloss Deep Burgundy	65011	Satin Black	65049
Satin Wine Red	65012	Flat Black	65050
Flat Merlot	65013	Metallic Gold	65051
Gloss Cherry	65014	Metallic Silver	65052
Gloss Berry	65015	Metallic Aluminum	65053
Flat Coral	65017	Gloss Clear	65058
Gloss Orange	65018	Satin Clear	65059
Gloss Salsa Orange	65019	Flat Clear	65060
Satin Cameo Pink	65020	Flat Dusty Jade	65081
Satin Glamour Pink	65021	Satin Summer Leaf	65082
Gloss Tulip Pink	65022	Satin Pistachio	65083
Satin Pale Lilac	65023	Satin Everglade	65084
Gloss Blue Lilac	65024	Gloss Dark Olive	65085
Satin Sumptuous Purple	65025	Satin Dusty Pink	65086
Satin Baby Blue	65026	Flat Black Plum	65087
Satin Aqua	65027	Gloss Deep Ocean	65088
Flat Teal	65028	Gloss Mediterranean	65089
Satin Navy	65029	Flat Driftwood	65090
Satin Rustic Blue	65030	Satin Warm Gray	65091
Gloss Royal Blue	65031	Flat Mellow Gold	65092
Gloss Pacific Blue	65032	Gloss Mustard Seed	65095
Flat Cool Jade	65033	Satin Real Red	65106
Satin Hunter Green	65034	Satin New Avocado	65200
Gloss Lawn Green	65035	Gloss Exotic Sea	65201
Gloss Garden Green	65036	Satin La Fond Cop	65202
Flat Sage	65037	Satin HH Maize	65203

### Typical Properties (65000 Gloss White)

#### Dry Time:

**To the touch:** 1 hours

**Recoat:** Within 4 hours or after 36 hours

#### Surface Coverage:

Coverage varies depending on surface color and porosity.

### Recommended Uses

- Metal
- Wood
- Plastic
- Many more surfaces

### Fill Weight

**Fill Weight:** 12 oz.

## Surface Preparation

Read the Lead Warning in Cautions section. Before applying, spray on an inconspicuous area to test for compatibility and suitability.

1. Surface should be clean and dry. Remove all dirt, grease, loose particles, wax, etc.
2. Use outdoors or in a well-ventilated area when temperature is between 65° and 90°F and humidity is below 60% to ensure proper drying.
3. Mask surrounding area on which spray may settle with newspapers or drop cloths.
4. Shake well, for at least 1 minute listening for the rattle of the mixing ball.
5. Hold can 8-10 inches from surface. Press spray button firmly.
6. Move can back and forth releasing button after each stroke. Overlap each stroke.
7. Two thin coats are recommended rather than one heavy coat.

## Cautions (65000 Gloss White)

**CONTAINS NO CFC's – in accordance with Federal regulations which prohibit the use of CFC propellants in aerosols.**

**WARNING: CONTAINS DIMETHYL KETONE, ISOBUTYL ACETATE, METHYL ISOBUTYL KETONE, XYLENE, ETHYLBENZENE.** Vapor Harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120 °F (49 °C). Replace cap after each use. **Vapors may ignite explosively.** Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing.

**Warning:** This product contains a chemical known to the state of California to cause cancer.

**NOTICE –** Reports have associated repeated or prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, **get medical attention immediately\***. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and **get medical attention\***; for skin, wash thoroughly with soap and water.

**\*Call poison control center, hospital emergency room or physician immediately.**

**DO NOT TAKE INTERNALLY.**

**KEEP OUT OF REACH OF CHILDREN.**

**For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.