

Safety Data Sheet acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

1 Identification

- **Product identifier**
- **Trade name:** *Tandus C-54 Seam Weld*
- **Relevant identified uses of the substance or mixture.** *Adhesive*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Royal Adhesives & Sealants, LLC
863 South East Main Street
Simpsonville, SC 29681
(864) 967-7691*
- **Supplier:**
*Tandus Centiva
A Tarkett Company*
- **Information department:** *Environment protection department.*
- **Emergency telephone number:**
*ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS02

- **Signal word** *Danger*
- **Hazard statements**
Highly flammable liquid and vapor.
- **Precautionary statements**
*Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Wear protective gloves / eye protection / face protection.
Ground/bond container and receiving equipment.
Keep container tightly closed.
Use only non-sparking tools.
Take precautionary measures against static discharge.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
In case of fire: Use for extinction: CO2, powder or water spray.*

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld

(Contd. of page 1)

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 3

Physical Hazard = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Hazardous components:**

78-93-3	methyl ethyl ketone	50-100%
109-99-9	tetrahydrofuran	25-50%
108-94-1	cyclohexanone	2.5-10%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Remove to fresh air. If not breathing, administer artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Call a doctor immediately.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

· **After swallowing:**

Immediately call a doctor.

Seek medical treatment.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
Avoid prolonged or repeated contact with skin.
Avoid contact with eyes.
Wash thoroughly after handling.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld

(Contd. of page 3)

· *Specific end use(s)* No further relevant information available.

8 Exposure controls/personal protection

· *Additional information about design of technical systems:* No further data; see item 7.· *Control parameters*· *Components with limit values that require monitoring at the workplace:*

78-93-3 methyl ethyl ketone

PEL Long-term value: 590 mg/m³, 200 ppmREL Short-term value: 885 mg/m³, 300 ppmLong-term value: 590 mg/m³, 200 ppmTLV Short-term value: 885 mg/m³, 300 ppmLong-term value: 590 mg/m³, 200 ppm

BEI

109-99-9 tetrahydrofuran

PEL Long-term value: 590 mg/m³, 200 ppmREL Short-term value: 735 mg/m³, 250 ppmLong-term value: 590 mg/m³, 200 ppmTLV Short-term value: 295 mg/m³, 100 ppmLong-term value: 147 mg/m³, 50 ppm

Skin

108-94-1 cyclohexanone

PEL Long-term value: 200 mg/m³, 50 ppmREL Long-term value: 100 mg/m³, 25 ppm

Skin

TLV Long-term value: 50 mg/m³, 20 ppm

Skin

· *Ingredients with biological limit values:*

78-93-3 methyl ethyl ketone

BEI 2 mg/L

Medium: urine

Time: end of shift

Parameter: MEK

109-99-9 tetrahydrofuran

BEI 2 mg/L

Medium: urine

Time: end of shift

Parameter: Tetrahydrofuran

108-94-1 cyclohexanone

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld

(Contd. of page 4)

BEI	80 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 1.2-Cyclohexanediol with hydrolysis (nonspecific, semi-quantitative)
	8 mg/L Medium: urine Time: end of shift Parameter: Cyclohexanol with hydrolysis (nonspecific, semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment (see listings below)**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

· **Body protection:**

- Protective work clothing
- Apron
- Emergency showers and eye wash stations should be available.

USA

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld

(Contd. of page 5)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point: Undetermined.

Boiling point: 67 °C (153 °F)

· **Flash point:** -14 °C (7 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 230 °C (446 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** May form explosive peroxides.

· **Flammable limits:**

Lower: 1.3 Vol %

Upper: 12.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 200 hPa (150 mm Hg)

· **Specific gravity at 20 °C (68 °F):** 0.94 g/cm³ (7.844 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 100.0 %

VOC (Per EPA 24) Not Available GMS/L

Solids content: not available

· **Other information** Grams VOC/Liter 672.0

Grams VOC/Liter [less water. less exempts] 672.0

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld

(Contd. of page 6)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:**
 - Strong oxidizers, acids, and bases.
 - Reacts with alkali and metals.
 - Reacts with halogenated compounds.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

78-93-3 methyl ethyl ketone

Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)

109-99-9 tetrahydrofuran

Oral	LD50	2500 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
 - Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product.
 - The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-94-1	cyclohexanone	3
----------	---------------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 1 (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld




(Contd. of page 7)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.
Disposal must be made according to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1133
- **UN proper shipping name**
- **DOT, IMDG, IATA** ADHESIVES
- **ADR** 1133 ADHESIVES
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** II
- **Environmental hazards:**
- **Marine pollutant:** Symbol (fish and tree)

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld

(Contd. of page 8)

- | | |
|--|----------------------------|
| · Special marking (ADR): | Symbol (fish and tree) |
| · Special precautions for user | Warning: Flammable liquids |
| · Danger code (Kemler): | 33 |
| · EMS Number: | F-E,S-E |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | UN1133, ADHESIVES, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· **New Jersey Right-to-Know List:**

None of the ingredients is listed.

· **New Jersey Special Hazardous Substance List:**

None of the ingredients is listed.

· **Pennsylvania Right-to-Know List:**

None of the ingredients is listed.

· **Pennsylvania Special Hazardous Substance List:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

78-93-3 methyl ethyl ketone

I

· **TLV (Threshold Limit Value established by ACGIH)**

109-99-9 tetrahydrofuran

A3

108-94-1 cyclohexanone

A3

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/20/2016

Revision Number 1

Revision Date 03/20/2016

Trade name: Tandus C-54 Seam Weld

(Contd. of page 9)

· MAK (German Maximum Workplace Concentration)

109-99-9	tetrahydrofuran	4
108-94-1	cyclohexanone	3B

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

 · **Department issuing SDS:** Environment protection department.

 · **Creation Date:** 02/28/2012

 · **Date of preparation / last revision** 03/20/2016 / -

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids, Hazard Category 2