

ASHLAND®		Page: 1
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ GENERAL MULTIPURPOSE GREASE

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ systemic toxicity - single exposure : Category 3 (Respiratory system)

GHS Label element

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.

ASHLAND®		Page: 2
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

Wear eye protection/ face protection.

Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	64742-65-0	Not a hazardous substance or mixture.	80.00
ASPHALTIC RESIN		Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335	24.99
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	Not a hazardous substance or mixture.	9.99

SECTION 4. FIRST AID MEASURES

ASHLAND®		Page: 3
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
acne
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local

ASHLAND®		Page: 4
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

- circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 Aldehydes
 Ketones
 Nitrogen oxides (NOx)
 Sulphur oxides
- Specific extinguishing methods :
- Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Ensure adequate ventilation.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
 Provide sufficient air exchange and/or exhaust in work rooms.

ASHLAND®		Page: 5
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE		Version: 1.0
VV608		

Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	64742-65-0	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS
		TWA	5 mg/m3 Inhalable fraction.	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an

ASHLAND®		Page: 6
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE		Version: 1.0
VV608		

approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Safety glasses
Skin and body protection	: Wear as appropriate: impervious clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures	: Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Physical state	: liquid
Colour	: amber
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 698 °F / 370 °C
Flash point	: 491 °F / 255 °C
Flammability (solid, gas)	: No data available

ASHLAND®		Page: 7
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : Not applicable

Relative density :
No data available

Density : 0.902 g/cm3 (20 °C)

Solubility(ies)
Water solubility : negligible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 315 °C

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products
carbon dioxide and carbon monoxide
Hydrocarbons

ASHLAND®		Page: 8
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate (Rat): 34,014 mg/kg

Acute inhalation toxicity : Acute toxicity estimate (Rat): 1,560 mg/l
Exposure time: 4 h

Acute dermal toxicity : Acute toxicity estimate (Rabbit): 8,261 mg/kg

Components:

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Acute oral toxicity : LD 50 (Rat): > 5 g/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Causes skin irritation.

Product:

Result: Irritating to skin

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED:

Result: Slightly irritating to skin

ASHLAND®		Page: 9
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

ASPHALTIC RESIN:
Result: Irritating to skin

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:
Species: Rabbit
Result: Not irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Result: Irritating to eyes

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED:
Result: Slightly irritating to eyes

ASPHALTIC RESIN:
Result: Irritating to eyes

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:
Species: Rabbit
Result: Mildly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED:
Genotoxicity in vitro : Test Type: Ames test
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

Product:

Assessment: May cause respiratory irritation.

Components:

ASPHALTIC RESIN:

ASHLAND®		Page: 10
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

Group 2B: Possibly carcinogenic to humans

ASPHALTIC RESIN

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

ASHLAND®		Page: 11
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 211

Persistence and degradability

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Biodegradability : Result: Inherently biodegradable
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ASHLAND®		Page: 12
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE		Version: 1.0
VV608		

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

ASHLAND®		Page: 13
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE VV608		Version: 1.0

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 Component(s) : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	64742-65-0	70.00 - 90.00 %
ASPHALTIC RESIN	Not Assigned	20.00 - 30.00 %
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	5.00 - 10.00 %

New Jersey Right To Know

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	64742-65-0	70.00 - 90.00 %
ASPHALTIC RESIN	Not Assigned	20.00 - 30.00 %
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	5.00 - 10.00 %

California Prop 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
KECL	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
AUSTR	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL.

Inventories

ASHLAND®		Page: 14
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE		Version: 1.0
VV608		

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/23/2015

NFPA:	HMIS III:						
Flammability Health Instability Special hazard.	<table border="1"> <tr> <td>HEALTH</td><td>2</td></tr> <tr> <td>FLAMMABILITY</td><td>1</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> 0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Sources of key data used to compile the Safety Data Sheet

Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

ASHLAND®		Page: 15
SAFETY DATA SHEET		Revision Date: 05/23/2015
		Print Date: 6/1/2015
		SDS Number: R0076417
Valvoline™ GENERAL MULTIPURPOSE GREASE		Version: 1.0
VV608		

CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System