

Manufacturer:
Xerox Corporation
Rochester, NY 14644

Telephone #(s): *Safety Information: (800) 828-6571*
Health Emergency:(585) 422- 2177
Transportation Emergency (Chemtrec):(800) 424 - 9300

Section I - Product Identification

Trade Names/Synonyms: 5090/S, DocuTech 135/4135/4635/5135/5135 PP/5135 NP/
5390/5690/6100/6115/6135/ 6155/ 6180/ DocuPrint 96 /115/
155 EPS/180 LPS DocuTech 128/155/180 HLC Black Dry Ink

Part No.: WH: 6R206;
XCI: 6R516*;
RX: 6R90100;
FX: 6R272
502S66183

Chemical Name: None

*Cancelled

WHMIS Status: This is not a WHMIS controlled product

Ingredients (% by wt.)

Styrene/butadiene copolymer (75-85%)
Ferric oxide (15-20%)
Carbon black (<5%)

CAS No.

9003-55-8
1317-61-9
1333-86-4

Section II - Emergency and First Aid

Eyes:

Flush with water.

Skin:

Wash with soap and water.

Inhalation:

Remove from exposure.

Ingestion:

Dilute stomach contents with several glasses of water.

Primary Route of Entry:

Inhalation

Symptoms of Overexposure:

Minimal respiratory tract irritation may occur as with exposure to large amounts of any non-toxic dust.

Medical Conditions Generally Aggravated by Exposure:

None when used as described by product literature.

Additional Information:

None

Section III - Toxicology and Health Information

The toxicology of this toner has been evaluated by Xerox Corporation. Data presented in this section is based on the test results of the toner or similar reprographic toners.

Oral LD₅₀: >5 g/kg (rats)

Dermal LD₅₀: >5 g/kg (rabbits)

Inhalation LC₅₀: >5 mg/l (rats, 4 hr exposure)
>20 mg/l (calculated 1 hr exposure)

Eye Irritation: Non-irritating (rabbits)

Skin Irritation: Non-irritating (rabbits, human patch)

Skin Sensitization: Non-sensitizing (guinea pigs; human patch)

Mutagenicity: No mutagenicity detected in Ames, Pol A+/A-, CHO/CA, and CHO/HGPRT.

Carcinogens: None known

Aquatic LC₅₀: >1000 mg/l (fathead minnows; rainbow trout)

TLV: 10 mg/m³ (total dust)

PEL: 15 mg/m³ (total dust)

5 mg/m³ (respirable dust)

STEL: N.E.

Ceiling: N.E.

XEL¹: 2.5 mg/m³ (total dust)

0.4 mg/m³ (respirable dust)

Additional Information: The results obtained from a Xerox sponsored Chronic Toner Inhalation Study, demonstrated no lung change in rats for the lowest (1mg/m³) exposure level (i.e. the level most relevant to potential human exposure). A very slight degree of fibrosis was noted in 25% of the animals at the middle (4mg/m³) exposure level, while a slight degree of fibrosis was noted in all the animals at the highest (16 mg/m³) exposure level. These findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged period. This study was conducted using a special test toner to comply with EPA testing protocol. The test toner was ten times more respirable than commercially available Xerox toner, and would not be functionally suitable for Xerox equipment.

¹XEL-Xerox Exposure Limit

XEROX Trade Name: 5090/S, DocuTech 135/4135/4635/5135/5135 PP/5135 NP/5390/5690/6100/6115/ **MSDS No.:** A-0058
6135/ 6155/ 6180/ DocuPrint 96/115/155 EPS/180 LPS DocuTech 128/155/
180 **HLC** Black Dry Ink

Section IV - Physical Data

Appearance/Odor:	Black powder /slight	Softening Range:	110-140°F (43-60°C)
Boiling Point:	N.A.	Melting Point:	N.A.
Solubility in Water:	Insoluble	Specific Gravity (H₂O=1):	~1
Evaporation Rate:	N.A.	Vapor Pressure (mm Hg):	N.A.
Vapor Density (Air=1):	N.A.	pH:	N.A.
Volatile:	N.A. % (Wt.) N.A. % (Vol.)		

Section V - Fire and Explosion Data

Flash Point (Method Used): N.A.
Flammable Limits: LEL: N.A., UEL: N.A.
NFPA 704: Health - 0, Fire - 1, Reactivity - 0
Extinguishing Media: Water, dry chemical, carbon dioxide or foam.
Special Fire Fighting Procedures: Avoid inhalation of smoke. Wear protective clothing and self-contained breathing apparatus.
Fire and Explosion Hazards: Toner is a combustible powder. Like most organic materials in powder form, it can form explosive mixtures when dispersed in air.

Section VI -Reactivity Data

Stability: Stable
Hazardous Polymerization: Will Not Occur
Hazardous Decomposition Products: Products of combustion may be toxic. Avoid breathing smoke.
Incompatibility (Materials to Avoid): None known

Section VII - Special Protection Information

Respiratory Protection: None required when used as intended in Xerox equipment.
Eye Protection: None required when used as intended in Xerox equipment.
Protective Gloves: None required when used as intended in Xerox equipment.
Other: For use other than normal customer - operating procedures (such as in bulk toner processing facilities), goggles and respirators may be required.

Section VIII - Special Precautions

Handling and Storage: None
Conditions to Avoid: Avoid prolonged inhalation of excessive dust.

Section IX- Spill, Leak, and Disposal Procedures

For Spills or Leakage: Sweep up or vacuum spilled toner and carefully transfer into sealable waste container. Sweep slowly to minimize generation of dust during clean-up. If a vacuum is used, the motor must be rated as dust tight. A conductive hose bonded to the machine should be used to reduce static buildup (See Section V). Residue can be removed with soap and cold water. Garments may be washed or dry cleaned, after removal of loose toner.

Waste Disposal Method: This material is not a hazardous waste according to Federal Regulation 40 CFR 261 when disposed. State and Local waste disposal requirements however, may be more restrictive. Consult with the appropriate State and Local authorities for specific information. Incinerate only in a closed container.

Section X - Transportation Information

DOT Proper Shipping Name: N.A. (Not Regulated) **ID Number:** N.A.
Hazard Classification: N.A. **Packing Group:** N.A.

600E54470