

Custodial

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION						
NFPA Rating: Health-2; Flammability-1; Reactivity-0; Special-G			HMIS Rating: Health-2; Flammability-1; Reactivity-0; Personal Protection-G			
Manufactured For: Triple S			DOT Hazard Classification: ORM-D			
Address: 2 Executive Park Dr.			Identity (trade name as used on label):			
Address: Billerica, MA 01862			CHEWING GUM REMOVER NF			
Phone: 978-667-7900			MSDS Number: 185 Revision- 1			
EMERGENCY RESPONSE NUMBER: 1-800-255-3924			Date Prepared: 10/15/97 Prepared By: DL			
NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA Information Calls: 978-667-7900						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
1,1,1,2-TETRAFLUOROETHANE		811-97-2	No	NE	NE	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A			Specific Gravity (H2O=1): Concentrate Only = N/A			
Vapor Pressure: PSIG @ 70°F (Aerosols): 80-100			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E			Evaporation Rate (= 1): N/E			
Solubility in Water:None			Water Reactive: No			
Appearance and Odor: Clear forceful spray, odorless.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE		Auto Ignition Temperature	Flammability Limits in Air by % in Volume:			
		N/E	% LEL: N/E % UEL: N/E			
FLASH POINT AND METHOD USED (non-aerosols): N/A			EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE			HAZARDOUS POLYMERIZATION <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Strong oxidizing agents.			Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE <input type="checkbox"/> NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Excessive inhalation of vapors can cause central nervous system depression with dizziness, confusion, incoordination, drowsiness or unconsciousness.						
Eye Contact: "Frostbite-like" effects may occur.			Skin Contact: "Frostbite-like" effects may occur.			
Ingestion: Not a route of entry.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation of vapors can cause central nervous system depression with dizziness, confusion, incoordination, drowsiness or unconsciousness. Irregular heartbeat with a strange sensation in the chest, "heart thumping", apprehension, lightheadedness, feeling of fainting, dizziness, weakness, sometimes progressing to loss of consciousness and death. Suffocation, if air is displaced by vapors.						
Medical Conditions Generally Aggravated by Exposure: Increased susceptibility to the effects of this material may be observed in persons with pre-existing disease of the central nervous system or cardiovascular system.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Flush with water for 15 minutes. Treat for frostbite if necessary by gently warming affected area. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: Not a potential route of entry.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH approved for organic vapor.						
Protective Gloves: Neoprene			Eye Protection: Safety glasses recommended.			
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 126°F. Avoid exposure to strong oxidizers.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.
 ** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only
 THIS MSDS IS CURRENT AS OF JANUARY 10, 2000. The DATE PREPARED section is the original date assembled and remains current until a change is necessary.